



CE SOLAR CHARGE CONTROLLER

*Cost-effective, Essential
LED Charge Controller*

Model Numbers

- CE-6
- CE-10
- CE-20
- CE-30
- CE-40

Works With

- Works as a stand-alone controller using internal settings.

Accessories & Options

- Evening or night light function pre-set in the factory or adjustable via the optional RC100

The Magnum Energy CE Series Charge Controllers by Sensata Technologies are an excellent, cost-effective choice for when simple controls and low self consumption are in order for your charge controller. Available in 6, 10, 20, 30, and 40 amp models, the pulse width modulated (PWM) CE Series automatically recognizes 12V or 24V systems and adjusts accordingly.

Product Features

- Serial topology with MOSFETs
- Automatic detection of voltage
- Voltage regulation
- PWM control
- Multistage charging technology
- Current compensated load disconnection
- Automatic load reconnection
- Temperature compensation
- Negative earthing of one or positive earthing of several terminals possible
- Monthly equalization charge

Displays

- Multifunction LED display
- Multi-colored LED
- 4 LEDs show operating states for operation, state of charge, fault messages

Electronic Protection Functions

- Overcharge protection
- Deep discharge protection
- Reverse polarity protection of module (≤ 36 V), load and battery
- Automatic electronic fuse
- Short circuit protection of load and module
- Overvoltage protection at module input
- Open circuit protection without battery
- Reverse current protection at night
- Overtemperature and overload protection
- Load disconnection on battery overvoltage



CE SOLAR CHARGE CONTROLLER SPECIFICATIONS

	CE-6	CE-10	CE-20	CE-30	CE-40
OPERATING PERFORMANCE					
System voltage	12 V (24 V)	12 V (24 V)	12 V (24 V)	12 V (24 V)	12 V (24 V)
Power consumption	< 4 mA	< 4 mA	< 4 mA	< 4 mA	< 10.5 mA
DC INPUT SIDE					
Open circuit voltage solar module (at minimum operating temperature)	< 47 V	< 47 V	< 47 V	< 47 V	<47 V
Module current	6 A	10 A	20 A	30 A	40 A
DC OUTPUT SIDE					
Load current	6 A	10 A	20 A	30 A	40 A
USB charge socket	n/a	n/a	n/a	n/a	5.2 V / 1.5 A
Reconnection voltage (LVR)	12.4 to 12.7 V (24.8 V to 25.4 V)	12.4 to 12.7 V (24.8 V to 25.4 V)	12.4 to 12.7 V (24.8 V to 25.4 V)	12.4 to 12.7 V (24.8 V to 25.4 V)	12.4 to 12.7 V (24.8 V to 25.4 V)
Deep discharge protection (LVD)	11.2 V to 11.6 V (22.4 V to 23.2 V)	11.2 V to 11.6 V (22.4 V to 23.2 V)	11.2 V to 11.6 V (22.4 V to 23.2 V)	11.2 V to 11.6 V (22.4 V to 23.2 V)	11.2 V to 11.6 V (22.4 V to 23.2 V)
BATTERY SIDE					
Battery voltage	n/a	n/a	9 V to 17 V (17.1 V to 34 V)	9 V to 17 V (17.1 V to 34 V)	9 V to 17 V (17.1 V to 34 V)
End-of-charge voltage	13.9 V (27.8 V)	13.9 V (27.8 V)	13.9 V (27.8 V)	13.9 V (27.8 V)	13.9 V (27.8 V)
Boost charge voltage	14.4 V (28.8 V)	14.4 V (28.8 V)	14.4 V (28.8 V)	14.4 V (28.8 V)	14.4 V (28.8 V)
Equalization charge	n/a	n/a	14.7 V (29.4 V)	n/a	n/a
Set battery type	gel	gel	flooded	flooded	flooded
Charge current	6 ADC	10 ADC	20 ADC	30 ADC	40 ADC
ENVIRONMENTAL SPECIFICATIONS					
Ambient temperature	-13° F to 122° F (-25° C to +50° C)				
PHYSICAL SPECIFICATIONS					
Terminal (fine/single wire)	AWG 12 / 9 (4 mm ² / 6 mm ²)	AWG 12 / 9 (4 mm ² / 6 mm ²)	AWG 6 / 4 (16 mm ² / 25 mm ²)	AWG 6 / 4 (16 mm ² / 25 mm ²)	AWG 6 / 4 (16 mm ² / 25 mm ²)
Degree of protection	IP 31	IP 31	IP 31	IP 31	IP 30
Dimensions (width x height x depth)	5.7" x 3.9" x 1.2" (145 mm x 100 mm x 30 mm)	5.7" x 3.9" x 1.2" (145 mm x 100 mm x 30 mm)	7.4" x 3.8" x 1.8" (187 mm x 96 mm x 45 mm)	7.4" x 3.8" x 1.8" (187 mm x 96 mm x 45 mm)	7.4" x 3.8" x 1.8" (187 mm x 97 mm x 45 mm)
Shipping dimensions (width x height x depth)	5.7" x 3.9" x 1.2" (147 mm x 100 mm x 31 mm)	5.7" x 3.9" x 1.2" (147 mm x 100 mm x 31 mm)	7.6" x 4.1" x 2" (195 mm x 105 mm x 50 mm)	7.6" x 4.1" x 2" (195 mm x 105 mm x 50 mm)	7.6" x 4.1" x 2" (195 mm x 105 mm x 50 mm)
Weight	.33 lb (150 g)	.33 lb (150 g)	.76 lb (345 g)	.76 lb (345 g)	.76 lb (345 g)
Shipping weight	.35 lb (160 g)	.35 lb (160 g)	.93 lb (420 g)	.93 lb (420 g)	.97 lb (440 g)
GENERAL SPECIFICATIONS					
Warranty	5 years	5 years	5 years	5 years	5 years

