

CMW SERIES INVERTER

Clean, Compact Power on the Go



Modified
Sine
Wave



Battery
Voltage
Options



Continuous
Output
Options

Model Numbers

- CMW412
- CMW1012
- CMW1512
- CMW3012H (hardwire)

Available For

- Emergency Medical Services
- Marine Systems
- Military Vehicles
- RV Systems
- Trucks
- Utility Vehicles

Available Accessories

- Remote Switch (CSW-RS)
- Transfer Switch (CSW-TS15)

The Magnum-Dimensions CMW Series inverter from Sensata Technologies is a cost effective modified sine wave inverter designed for clean, compact power on the go. The CMW will safely run many small appliances and provide you with reliable AC power for troublefree use.

FEATURES

Compact and Lightweight

The CMW provides pure sine wave power from a small footprint designed to fit in tight vehicle and marine spaces. And it is lightweight, so won't weigh you down.

At-a-Glance Status

The inverter's status can be determined at a glance with the easy to read LED light.

Digital Display

The alphanumeric display shows the inverter's battery voltage, total AC output power, along with additional operation codes.

USB Port

Power and charge your USB-enabled device with the available USB port.

GFCI AC Outlet

Plug in two pieces of equipment directly to the CMW and know that the GFCI outlet will quickly stop the flow of electricity should a ground fault occur. The outlet also comes with an LED indicator and test/reset capability.

Automatic Transfer Switch Option

The CMW3012H automatically switches between shore power and inverter/battery power.

AC Wiring Access Cover

The CMW3012H provides access to the AC wiring terminals to allow for hardwiring the AC output.



OPTIONS

Remote Switch


Use the optional CSW-RS remote switch for even easier on/off access away from the inverter. The CSW-RS comes with a 20' cable.



Transfer Switch

Use the optional 15 amp CSW-TS15 transfer switch to automatically switch AC load connections between utility/generator power and the AC output of the CMW inverters.

CMW SERIES SPECIFICATIONS



	CMW412	CMW1012	CMW1512	CMW3012H
INVERTER SPECIFICATIONS - OUTPUT				
Continuous power at nominal DC voltage	400 watts	1000 watts	1500 watts	3000 watts
Peak surge power	800 watts	2000 watts	3000 watts	6000 watts
Continuous current at 12.5 V	38 A	96 A	140 A	280 A
AC output voltage at 12.5 VDC	120 VAC \pm 5%	120 VAC \pm 5%	120 VAC \pm 5%	120 VAC \pm 5%
AC output current	3.3 AAC	8.3 AAC	12.5 AAC	25.0 AAC
AC output voltage range	104 - 127 VAC	104 - 127 VAC	104 - 127 VAC	104 - 127 VAC
AC output frequency	60 Hz \pm 0.5 Hz	60 Hz \pm 0.5 Hz	60 Hz \pm 0.5 Hz	60 Hz \pm 0.5 Hz
AC output waveform	Modified sine wave	Modified sine wave	Modified sine wave	Modified sine wave
USB	NA	5 V, 750 mA	5 V, 750 mA	5 V, 750 mA
INVERTER SPECIFICATIONS - INPUT				
Nominal DC input voltage	12.5 VDC	12.5 VDC	12.5 VDC	12.5 VDC
DC input voltage range	10.5 - 15.5 VDC	10.5 - 15.5 VDC	10.5 - 15.5 VDC	10.5 - 15.5 VDC
No load draw	< 0.3 ADC	< 0.6 ADC	< 0.6 ADC	< 1.5 ADC
High voltage shutdown	15.5 VDC	15.5 VDC	15.5 VDC	15.5 VDC
Low voltage alarm	11.2 VDC	11.2 VDC	11.2 VDC	11.0 VDC SdL / 12.1 VDC SdH
Low voltage shutdown	10.5 VDC	10.5 VDC	10.5 VDC	10.5 VDC SdL / 11.8 VDC SdH
Low voltage recovery	11.8 VDC	11.8 VDC	11.8 VDC	12.0 VDC SdL / 12.6 VDC SdH
GENERAL FEATURES AND CAPABILITIES				
Output power warning	NA	Yes, with warning code	Yes, with warning code	Yes, with warning code
Output power shutdown	Yes	Yes, with shutdown code	Yes, with shutdown code	Yes, with shutdown code
Temperature warning	NA	Yes, with warning code	Yes, with warning code	Yes, with warning code
Temperature shutdown	Yes	Yes, with shutdown code	Yes, with shutdown code	Yes, with shutdown code
Display status indictator	LED: Power, Fault	LED: Power, Fault	LED: Power, Fault	LED: Power, Fault
Digital display	None	Volts in, power out, error codes	Volts in, power out, error codes	Volts in, power out, error codes
AC receptacles	NEMA 5-15	Dual GFCI w/ LED indicator	Dual GFCI w/ LED indicator	NEMA 5-20, Dual GFCI w/ LED indicator
Listings	Conforms to UL458, Certified to CSA STD C22.2 No. 107.1			
Warranty	One year	One year	One year	One year
ENVIRONMENTAL SPECIFICATIONS				
Operating temperature	-0° C to +40° C (32° F to 104° F)			
PHYSICAL SPECIFICATIONS				
Dimensions (l x w x h)	7.3" x 4.1" x 2.1" (18.5 cm x 10.4 cm x 5.3 cm)	12.63" x 6.9" x 3.5" (32.1 cm x 17.5 cm x 8.9 cm)	15.0" x 6.9" x 3.5" (38.1 cm x 17.5 cm x 8.9 cm)	19.0" x 9.0" x 4.5" (48.3 cm x 23.0 cm x 11.5 cm)
Weight	1.6 lb (.7 kg)	5.3 lb (2.4 kg)	6.9 lb (3.1 kg)	13.0 lb (5.9 kg)



OFFICES
 2211 West Casino Road
 Everett, Washington 98204 USA
 425-353-8833

4467 White Bear Pkwy
 St. Paul, MN 55110 USA
 800-553-6418

www.SensataPower.com

Testing for specifications at 25° C.
 Specifications subject to change without notice.

February 2017 Rev A Part #131453