


ME-RVC | BRIDGE MODULE

Introduction

The ME-RVC bridge module converts proprietary MagNet data to the commonly used RV-C communications protocol, allowing Magnum Energy brand inverters and accessories to communicate with RV-C compliant devices.



Features

- Connect up to two Magnum Energy brand inverter/chargers to one module.
- Emulates the Magnum Energy ME-RC remote control, to allow RV-C control of the features and settings in the inverter and in the ME-AGS and ME-BMK accessories.
- If using the ME-RVC bridge module with MS or MMS Series inverter/chargers, easily choose from and set standard battery profiles, including Lithium Iron Phosphate (LFP), Gel, Flooded, AGM1, and AGM2 from appropriate RV-C compliant devices.

Model Numbers

- ME-RVC

Works With

- ME Series
- MM Series
- MMS Series
- MS Series
- MS-PAE Series
- RD Series



SPECIFICATIONS

SPECIFICATIONS	
Input voltage*	8 – 17 VDC
Input amps	40 mA typical, 60 mA at 12V
Operating temperature range	-4° F to 140° F (-20° C to +60° C)
EEPROM	None
Source address	66
SAE J1939	593
Environmental limitations	Not sealed for exterior mounting
Dimensions (L x W x D)	5.38" x 3.25" x 1.25" (13.65 cm x 8.23 cm x 3.18 cm)

* Powered only from the RV-C connector

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

CONTACT US

651-653-7000
800-553-6418
InverterInfo@sensata.com

Power Conversion
www.magnum-dimensions.com