



## MMS SERIES | INVERTER/CHARGER

SINE WAVE POWER FOR MOBILE APPLICATIONS

### Introduction

The MMS Series inverter/charger is a pure sine wave inverter providing a cost effective solution for those with smaller power needs in mobile applications. Versatile, easy-to-use, and lightweight, the MMS Series provides a reliable base for energy systems. The built-in Power Factor Corrected (PFC) charger uses 25-30% less energy from a generator than a standard charger. The hourglass case, paired with the die cast aluminum base combines form with function, creating an attractive unit that uses its base as a heat sink for superior high temperature operation.



### Features

- Battery Profile Presets – Using the ME-RC, ME-ARC, or ME-MR Remote Controls, easily choose from and set standard battery profiles, including Lithium Iron Phosphate (LFP) – only available via the ME-RC and ME-MR, Gel, Flooded, AGM1, and AGM2.
- Versatile Mounting – Mount the MMS Series on a shelf, bulkhead, or even upside down.
- Fan Cooled – The MMS Series is fan cooled, enabling the unit to work well in confined spaces. If the inverter does exceed its temperature limits, it will automatically shut down and then restart when it cools down.
- Convenient Switches – The MMS Series comes with an on/off front-mounted switch with an easy-to-read LED indicator.
- Circuit Breaker Protection – This model comes with built in input and output circuit breakers for ease of installation.
- Battery Temp Sensor – The standard battery temp sensor monitors temperatures from 0 - 50° C.
- Buy with Ease – The MMS Series is backed by a two-year (24-month) parts and labor warranty.

### Model Numbers

- MMS1012
- MMS1012-G

### Available For

- Emergency Vehicles
- Marine Systems
- RV Systems

### Available Accessories

- DC Load Disconnect
- Fuse Blocks
- MagWeb
- Remote - ME-ARC
- Remote - ME-MR
- Remote - ME-RC
- Remote - MM-RC



Pure Sine Wave



Battery Voltage Options



Continuous Output Options



## SPECIFICATIONS

	MMS1012	MMS1012-G
<b>INVERTER SPECIFICATIONS</b>		
<b>Input battery voltage range</b>	9 to 17 VDC	9 to 17 VDC
<b>Nominal AC output voltage</b>	120 VAC ± 5%	120 VAC ± 5%
<b>Output frequency and accuracy</b>	60 Hz ± 0.1 Hz	60 Hz ± 0.1 Hz
<b>Total Harmonic Distortion (THD)</b>	< 5%	< 5%
<b>1 msec surge current (amps AC)</b>	38	38
<b>100 msec surge current (amps AC)</b>	21	21
<b>5 sec surge power (real watts)</b>	1750	1750
<b>30 sec surge power (real watts)</b>	1600	1600
<b>5 min surge power (real watts)</b>	1200	1200
<b>30 min surge power (real watts)</b>	1050	1050
<b>Output power (continuous watts)</b>	1000	1000
<b>Maximum continuous input current</b>	133 ADC	133 ADC
<b>Inverter efficiency (peak)</b>	87%	87%
<b>Transfer time</b>	16 msec	16 msec
<b>Search mode (typical)</b>	5 watts	5 watts
<b>No load (120 VAC output, typical)</b>	19 watts	19 watts
<b>Waveform</b>	Pure Sine Wave	Pure Sine Wave
<b>CHARGER SPECIFICATIONS</b>		
<b>Continuous output at 25° C</b>	50 ADC	50 ADC
<b>Charger efficiency</b>	84%	84%
<b>Power factor</b>	> .95	> .95
<b>Input current at rated output (AC amps)</b>	7	7
<b>GENERAL FEATURES AND CAPABILITIES</b>		
<b>Transfer relay capability</b>	20 AAC (input current for charging and pass through)	
<b>Battery temperature compensation</b>	Yes, 15 ft Battery Temp Sensor standard	
<b>Internal cooling</b>	0 to 59 cfm variable speed	
<b>Overcurrent protection</b>	Yes, with two overlapping circuits	
<b>Overtemperature protection</b>	Yes, on transformer and MOSFETS	
<b>On/Off with status indicator</b>	Yes, front mounted and easily accessible	
<b>Low battery cutout</b>	10 VDC, adjustable with the ME-RC remote	
<b>AC output/AC input</b>	Hardwire/Hardwire	GFCI/3 ft cord
<b>Output circuit breaker/Input circuit breaker</b>	15A/20AAC	NA/15AAC
<b>Listings</b>	ETL Listed to UL/cUL1741 and UL/cUL458, CSA C22.2 #107.1-01, meets KKK-A-1822E standard	

<b>Warranty</b>	Two years
<b>ENVIRONMENTAL SPECIFICATIONS</b>	
<b>Temperature (Operating/Non-operating)</b>	-20° C to +60° C (-4° F to 140° F) to -40° C to +70° C (-40° F to 158° F)
<b>Operating humidity</b>	0 to 95% RH non-condensing
<b>PHYSICAL SPECIFICATIONS</b>	
<b>Dimensions (l x w x h)</b>	16.6" x 8.4" x 4.7" (42 cm x 21 cm x 12 cm)
<b>Mounting</b>	Shelf (top or bottom up) or bulkhead (vents up)
<b>Weight</b>	23 lb (10.4 kg)
<b>Shipping weight</b>	25 lb (11.3 kg)
<b>Max operating altitude</b>	15,000' (4570 m)
<b>Construction</b>	ABS plastic top and cast aluminum bottom



## GENERAL NOTES

Testing for specifications at 25° C.  
Specifications subject to change without notice.



## AGENCY APPROVALS & CERTIFICATIONS

- ETL Listed to UL/cUL1741 and UL/cUL458, CSA C22.2 #107.1-01, meets KKK-A-1822E standard

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

## CONTACT US

651-653-7000  
800-553-6418  
[InverterInfo@sensata.com](mailto:InverterInfo@sensata.com)

**Power Conversion**  
[www.magnum-dimensions.com](http://www.magnum-dimensions.com)